```
   -> 0.0013s
== 20250420191846 CreateActiveStorageTables: migrated (0.0029s)
=============

== 20250420191847 CreateActionMailboxTables: migrating
======================
-- create_table(:action_mailbox_inbound_emails)
   -> 0.0017s
== 20250420191847 CreateActionMailboxTables: migrated (0.0017s)
=============
```

In the real world, we'd also need to configure Action Mailbox for our particular incoming email service provider. The Rails Guide[85] is the best place to look for how to do that. We won't set one up here since setting up accounts with services like Amazon SES or Mailgun is somewhat involved (though once you have your account set up, configuring Rails to use it is a snap). For our immediate needs, Rails provides a way to simulate sending emails, which we'll see in a moment.

The way Action Mailbox works is that all incoming emails get stored in a cloud storage system like Amazon's S3. Rails includes a library called Active Storage that abstracts away the details of the cloud service you're using.

Active Storage Configuration

As with your real-world email provider, your real-world cloud storage provider will require specific configuration in Rails, which we'll do in *Configure Active Storage*. For development purposes, we'll use the disk-based service that works with our local disk. This will allow us to fully use Active Storage locally, which means Action Mailbox can work locally.

Rails has already preconfigured the development and test environments for you to use Active Storage.

If you take a peek in `config/environments/development.rb`, you'll see: