with a cloud storage provider and store a reference to that object in the database.

Now that we've done the one-time setup, let's create a mailbox to receive our support request emails from customers.

Creating a Mailbox to Receive Emails

Action Mailbox works by routing incoming emails to a mailbox. A mailbox is a subclass of `ApplicationMailbox` with a method named `process` that's called for each email routed to that mailbox. The way emails get routed is similar to how web requests get routed in `config/routes.rb`. For email, you'll tell Rails what sorts of emails you want routed where.

We want emails to `support@example.com` to get routed to a mailbox so we can handle them. The way to do that is to insert a call to the method `routing` inside `ApplicationMailbox`:

rails80/depot_ta/app/mailboxes/application_mailbox.rb

```
class ApplicationMailbox < ActionMailbox::Base
  # routing /something/i => :somewhere

» routing "support@example.com" => :support
end
```

This tells Rails that any email to (or cc'd to) `support@example.com` should be handled by the class `SupportMailbox`. We can create that class using a Rails generator:

```
> bin/rails generate mailbox support
      create  app/mailboxes/support_mailbox.rb
      invoke  test_unit
      create    test/mailboxes/support_mailbox_test.rb
```

If you look at `app/mailboxes/support_mailbox.rb`, you'll see a few lines of code, notably an empty method called `process`: