```
»     receive_inbound_email_from_mail(
»       to: "support@example.com",
»       from: "chris@somewhere.net",
»       subject: "Need help",
»       body: "I can't figure out how to check out!!"
»     )
»
»     support_request = SupportRequest.last
»     assert_equal "chris@somewhere.net", support_request.email
»     assert_equal "Need help", support_request.subject
»     assert_equal "I can't figure out how to check out!!", support_request.
  body
»     assert_nil support_request.order
»   end

  end
```

If we run this test now, it should pass:

```
> bin/rails test test/mailboxes/support_mailbox_test.rb
Run options: --seed 26908

# Running:

.

Finished in 0.322222s, 3.1035 runs/s, 12.4138 assertions/s.
1 runs, 4 assertions, 0 failures, 0 errors, 0 skips
```

Great! For the second test, we'll need to create a few orders before we send the email. You'll recall from*Test Fixtures*, that we can use fixtures to set up test data in advance. We have one we can use already, but ideally, we'd have a total of two orders for the user sending the email and a third order from another user. That would validate that we're both searching for the right user *and* selecting the most recent order.

Let's add two new fixtures to **test/fixtures/orders.yml**

rails80/depot_tb/test/fixtures/orders.yml

```
# Read about fixtures at
```