```
# Make sure RUBY_VERSION matches the Ruby version in .ruby-version
ARG RUBY_VERSION=3.4.3
FROM docker.io/library/ruby:$RUBY_VERSION-slim AS base

# Rails app lives here
WORKDIR /rails

# Install base packages
RUN apt-get update -qq && \
    apt-get install --no-install-recommends -y curl libjemalloc2 \
      libvips sqlite3 && \
    rm -rf /var/lib/apt/lists /var/cache/apt/archives

# Set production environment
ENV RAILS_ENV="production" \
    BUNDLE_DEPLOYMENT="1" \
    BUNDLE_PATH="/usr/local/bundle" \
    BUNDLE_WITHOUT="development"
```

This part contains five *instructions*, each of which by convention is capitalized. The first instruction is `ARG`, which defines a variable that can be used in subsequent instructions. The second instruction is `FROM`, which specifies the base image to build upon. Taken together, they instruct Docker to start with an image that has Ruby 3.4.3 installed. You can find the image on Docker Hub.[88]

The third instruction is `WORKDIR`, which creates and sets the current working directory.

The fourth instruction is `RUN`, which runs a series of commands. The first command updates the package list, and the second installs a number of packages. The third command cleans up files that are no longer necessary.

While the full `ruby` image contains everything you *might* need, including plenty that you'll never use, `ruby:slim` doesn't contain things that will be needed to generate your demo application—things like `make` and `git`.