```
    useradd rails --uid 1000 --gid 1000 --create-home --shell \
      /bin/bash && \
    chown -R rails:rails db log storage tmp
USER 1000:1000

# Entrypoint prepares the database.
ENTRYPOINT ["/rails/bin/docker-entrypoint"]

# Start server via Thruster by default, this can be overwritten at
#   runtime
EXPOSE 80
CMD ["./bin/thrust", "./bin/rails", "server"]
```

Next, the installed gems and the application code are copied from the build image to the final deploy image.

A non-root user is then created, and only specific directories are owned by that user. This is a security measure to prevent an attacker from gaining access to the entire system if they manage to break out of the application.

An `ENTRYPOINT` is defined that will set up the application. This is a separate script that will set up `libjemalloc2` and then run the database preparation commands.

`EXPOSE 80` identifies the port that the Thruster HTTP/2 proxy will be listening on.

Finally, the `CMD` instruction specifies the command that will be run when the container is started. In this case, it runs Thruster. The last two entries in the CMS list are arguments to Thruster, which is the command to start the Rails server and the parameter to pass to Rails. Note that this is *not* the `bin/dev` command as that command is only used in development.

## Using Thruster as an HTTP/2 Proxy

Thruster is a high-performance HTTP/2 proxy that can be used to serve your application. It's a good choice for serving Rails applications as it can handle