```
master_key:
  file: ./config/master.key
```

The general pattern of placing a secret in a file, listing all of the secrets you'll be using in one place, and then referencing individual secrets by the containers that use them is common in cloud deployments. Rails makes it easy in that there's only one secret you need for Rails applications, namely a master key. That key can be used to unlock all of the credentials that you'll need.

Configuring SSL

When you deploy your application to the web, you'll want to use SSL. SSL is a protocol that encrypts the data between the client and the server. But for now, we're going to disable SSL. This is because we're deploying to a local machine. SSL isn't needed for local deployments.

In config/environments/production.rb edit the following line to disable SSL:

```
  # Force all access to the app over SSL, use Strict-Transport-Security,
  # and use secure cookies.
» config.force_ssl = !ENV["RAILS_MASTER_KEY"].nil?
```

Note that this checks for a RAILS_MASTER_KEY environment variable. This will be set when you deploy using Kamal or Cloud hosting providers. It won't be set when you deploy locally.

Getting Up and Running

We've covered a lot of ground. Whether you skimmed or read every word in the preceding sections, you can see that a lot of thought and expertise has gone into the creation of the Dockerfile that Rails provides.

Now it's time to get things up and running. The first thing we need to do is install Docker itself. You can get it at the Docker website.[91]