```
»   host: depot.example.com

  # Credentials for your image host.
  registry:
    # Specify the registry server, if you're not using Docker Hub
    # server: registry.digitalocean.com / ghcr.io / ...
»   username: samruby

    # Always use an access token rather than real password when possible.
    password:
      - KAMAL_REGISTRY_PASSWORD

  # Inject ENV variables into containers (secrets come from .kamal/secrets).
  env:
    secret:
      - RAILS_MASTER_KEY
»     - ACCESS_KEY_ID
»     - SECRET_ACCESS_KEY
»     - ENDPOINT_URL_S3
»     - REGION
»     - BUCKET_NAME
    clear:
      # Run the Solid Queue Supervisor inside the web server's Puma process to
      # do jobs.  When you start using multiple servers, you should split out
      # job processing to a dedicated machine.
      SOLID_QUEUE_IN_PUMA: true

      # Set number of processes dedicated to Solid Queue (default: 1)
      # JOB_CONCURRENCY: 3

      # Set number of cores available to the application on each server
      # (default: 1).
      # WEB_CONCURRENCY: 2

      # Match this to any external database server to configure Active Record
      # correctly. Use work-db for a db accessory server on same machine via
      #  local kamal docker network.

      # Log everything from Rails
      # RAILS_LOG_LEVEL: debug

  # Aliases are triggered with "bin/kamal <alias>".
  # You can overwrite arguments on invocation:
```