```
  # "bin/kamal logs -r job" will tail logs from the first server
  # in the job section.
  aliases:
    console: app exec --interactive --reuse "bin/rails console"
    shell: app exec --interactive --reuse "bash"
    logs: app logs -f
    dbc: app exec --interactive --reuse "bin/rails dbconsole"


  # Use a persistent storage volume for sqlite database files
  # and local Active Storage files.
» # Recommended to change this to a mounted volume path that is backed
» # up off server.
  volumes:
    - "work_storage:/rails/storage"


  # Bridge fingerprinted assets, like JS and CSS, between versions to avoid
  # hitting 404 on in-flight requests. Combines all files from new and old
  # version inside the asset_path.
  asset_path: /rails/public/assets

  # Configure the image builder.
  builder:
    arch: amd64
»   context: .
»   remote: ssh://root@192.168.0.1
»   local: false

    # # Build image via remote server (useful for faster amd64 builds on
    # # arm64 computers)
    # remote: ssh://docker@docker-builder-server
    #
    # # Pass arguments and secrets to the Docker build process
    # args:
    #   RUBY_VERSION: ruby-3.4.3
    # secrets:
    #   - GITHUB_TOKEN
    #   - RAILS_MASTER_KEY

» # Configure logging
» logging:
»   driver: local
```