While not related to data you've captured, aliases[120] are useful for commands that you're likely to repeat.

Secrets

In your config/deploy.yml you listed your secrets but not their values. Those values are extracted using a script that you can find in .kamal/secrets.

rails80/depot_td/.kamal/secrets

```
# Secrets defined here are available for reference under registry/password,
# env/secret, builder/secrets, and accessories/*/env/secret in
# config/deploy.yml. All secrets should be pulled from either password
# manager, ENV, or a file. DO NOT ENTER RAW CREDENTIALS HERE! This file
# needs to be safe for git.

# Example of extracting secrets from 1password (or another compatible
# pw manager)
» SECRETS=$(kamal secrets fetch --adapter 1password --account your-account  \
»   --from Vault/Item KAMAL_REGISTRY_PASSWORD RAILS_MASTER_KEY \
»   ACCESS_KEY_ID SECRET_ACCESS_KEY ENDPOINT_URL REGION BUCKET_NAME)
»
» KAMAL_REGISTRY_PASSWORD=$(kamal secrets extract KAMAL_REGISTRY_PASSWORD
»                           ${SECRETS})
» RAILS_MASTER_KEY=$(kamal secrets extract RAILS_MASTER_KEY ${SECRETS})
» ACCESS_KEY_ID=$(kamal secrets extract ACCESS_KEY_ID ${SECRETS})
» SECRET_ACCESS_KEY=$(kamal secrets extract SECRET_ACCESS_KEY ${SECRETS})
» ENDPOINT_URL=$(kamal secrets extract ENDPOINT_URL ${SECRETS})
» REGION=$(kamal secrets extract REGION ${SECRETS})
» BUCKET_NAME=$(kamal secrets extract BUCKET_NAME ${SECRETS})

# Use a GITHUB_TOKEN if private repositories are needed for the image
# GITHUB_TOKEN=$(gh config get -h github.com oauth_token)

# Grab the registry password from ENV
» # KAMAL_REGISTRY_PASSWORD=$KAMAL_REGISTRY_PASSWORD

# Improve security by using a password manager.
# Never check config/master.key into git!
» # RAILS_MASTER_KEY=$(cat config/master.key)
```