```
# Use bin/rails credentials:edit to set the AWS secrets
# (as aws:access_key_id|secret_access_key)
# amazon:
#   service: S3
#   access_key_id: <%= Rails.application.credentials
                        .dig(:aws, :access_key_id) %>
#   secret_access_key: <%= Rails.application.credentials
                            .dig(:aws, :secret_access_key) %>
#   region: us-east-1
#   bucket: your_own_bucket-<%= Rails.env %>

# Remember not to checkin your GCS keyfile to a repository
# google:
#   service: GCS
#   project: your_project
#   credentials: <%= Rails.root.join("path/to/gcs.keyfile") %>
#   bucket: your_own_bucket-<%= Rails.env %>

# Use bin/rails credentials:edit to set the Azure Storage secret
# (as azure_storage:storage_access_key)
# microsoft:
#   service: AzureStorage
#   storage_account_name: your_account_name
#   storage_access_key: <%= Rails.application.credentials
                  .dig(:azure_storage, :storage_access_key) %>
#   container: your_container_name-<%= Rails.env %>

# mirror:
#   service: Mirror
#   primary: local
#   mirrors: [ amazon, google, microsoft ]
```

Note that if you used the Rails credentials file, you can use the `Rails.application.credentials` hash to extract these values. The `amazon` example in this file uses this approach.

Finally, update your `config/environments/production.rb` to use the S3 service:

rails80/depot_td/config/environments/production.rb

```
»   # Store uploaded files in S3 object storage
```