- While Rails selected some good defaults for rubocop, ruby gems doesn't follow them. Try running `rubocop -A` to correct this, or tell rubocop to ignore this error in the `.rubocop.yml`:

rails80/depot_td/.rubocop.yml

```
» # Avoid flagging bundler added statements
» Style/HashSyntax:
»   Exclude:
»   - Gemfile
```

Footnotes

[88] https://hub.docker.com/_/ruby

[89] https://packages.debian.org/stable/allpackages

[90] https://github.com/Shopify/bootsnap?tab=readme-ov-file#bootsnap-for-rails

[91] https://docs.docker.com/get-docker/

[92] https://kamal-deploy.org/

[93] https://kamal-deploy.org/docs/

[94] https://kamalmanual.com/handbook/

[95] https://docs.github.com/en/authentication/connecting-to-github-with-ssh/generating-a-new-ssh-key-and-adding-it-to-the-ssh-agent

[96] https://www.hetzner.com/

[97] https://www.digitalocean.com/resources/articles/hetzner-alternatives

[98] https://fractaledmind.github.io/2023/12/23/rubyconftw/

[99] https://www.cloudflare.com/products/registrar/

[100] https://www.shopify.com/blog/best-domain-registrars#

[101] https://hub.docker.com/

[102] https://quay.io/

[103] https://cloud.google.com/artifact-registry/docs