code that generates receipts, customs documentation for shipping, and other PDF-formatted documentation is in the directory `lib/pdf_stuff`.

In previous versions of Rails, the files in the `lib` directory were automatically included in the load path used to resolve `require` statements. This is now an option that you need to explicitly enable. To do so, place the following in `config/application.rb`:

```
config.autoload_paths += %W(#{Rails.root}/lib)
```

Once you have files in the `lib` directory and the `lib` added to your autoload paths, you can use them in the rest of your application. If the files contain classes or modules and the files are named using the lowercase form of the class or module name, then Rails will load the file automatically. For example, we might have a PDF receipt writer in the file `receipt.rb` in the directory `lib/pdf_stuff`. As long as our class is named `PdfStuff::Receipt`, Rails will be able to find and load it automatically.

For those times where a library can't meet these automatic loading conditions, you can use Ruby's `require` mechanism. If the file is in the `lib` directory, you can require it directly by name. For example, if our Easter calculation library is in the file `lib/easter.rb`, we can include it in any model, view, or controller using this:

```
require "easter"
```

If the library is in a subdirectory of `lib`, remember to include that directory's name in the `require` statement. For example, to include a shipping calculation for airmail, we might add the following line:

```
require "shipping/airmail"
```

A Place for Our Rake Tasks

You'll also find an empty `tasks` directory under `lib`. This is where you can write your own Rake tasks, allowing you to add automation to your project.