```
    end
  end
end
```

Let's use the handy-dandy `bin/rails console` command to play with this model. First, we'll ask for a list of column names:

```
depot> bin/rails console
Loading development environment (Rails 8.0.2)
3.1.3 :001 > Order.column_names
=> ["id", "name", "address", "email", "pay_type", "created_at",
"updated_at"]
```

Then we'll ask for the details of the `pay_type` column:

```
>> Order.columns_hash["pay_type"]
 =>
#<ActiveRecord::ConnectionAdapters::Column:0x00000001094cc200
 @collation=nil,
 @comment=nil,
 @default=nil,
 @default_function=nil,
 @name="pay_type",
 @null=true,
 @sql_type_metadata=
  #<ActiveRecord::ConnectionAdapters::SqlTypeMetadata:0x00000001094dc178
   @limit=nil,
   @precision=nil,
   @scale=nil,
   @sql_type="integer",
   @type=:integer>>
```

Notice that Active Record has gleaned a fair amount of information about the `pay_type` column. It knows that it's an integer, it has no default value, it isn't the primary key, and it may contain a null value. Rails obtained this information by asking the underlying database the first time we tried to use the `Order` class.

The attributes of an Active Record instance generally correspond to the data in the corresponding row of the database table. For example, our `orders` table