```
orders = LineItem.find_by_sql("select line_items.* from line_items, orders "
+
                              " where order_id = orders.id                  "
+
                              "   and orders.name = 'Dave Thomas'           "
)
```

Only those attributes returned by a query will be available in the resulting model objects. We can determine the attributes available in a model object using the `attributes`, `attribute_names`, and `attribute_present?` methods. The first returns a hash of attribute name-value pairs, the second returns an array of names, and the third returns `true` if a named attribute is available in this model object:

rails80/e1/ar/find_examples.rb

```
orders = Order.find_by_sql("select name, pay_type from orders")
first = orders[0]
p first.attributes
p first.attribute_names
p first.attribute_present?("address")
```

This code produces the following:

```
{"name"=>"Dave Thomas", "pay_type"=>"check"}
["name", "pay_type"]
false
```

`find_by_sql` can also be used to create model objects containing derived column data. If we use the `as xxx` SQL syntax to give derived columns a name in the result set, this name will be used as the name of the attribute:

rails80/e1/ar/find_examples.rb

```
items = LineItem.find_by_sql("select *,                                  " +
                             "  products.price as unit_price,            " +
                             "  quantity*products.price as total_price,  " +
                             "  products.title as title                  " +
                             " from line_items, products                 " +
                             " where line_items.product_id = products.id ")
```