file is rendered without using the current layout. This can be overridden with `layout: true`.

render(partial: name, …)
: Renders a partial template. We talk about partial templates in depth in *Partial-Page Templates*.

render(nothing: true)
: Returns nothing—sends an empty body to the browser.

render(xml: stuff)
: Renders *stuff* as text, forcing the content type to be `application/xml`.

render(json: stuff, [callback: hash])
: Renders *stuff* as JSON, forcing the content type to be `application/json`. Specifying `:callback` will cause the result to be wrapped in a call to the named callback function.

render(:update) do |page| … end
: Renders the block as an RJS template, passing in the page object.

```
render(:update) do |page|
  page[:cart].replace_html partial: 'cart', object: @cart
  page[:cart].visual_effect :blind_down if @cart.total_items == 1
end
```

All forms of `render` take optional `:status`, `:layout`, and `:content_type` parameters. The `:status` parameter provides the value used in the status header in the HTTP response. It defaults to `"200 OK"`. Do not use `render` with a 3xx status to do redirects; Rails has a `redirect` method for this purpose.

The `:layout` parameter determines whether the result of the rendering will be wrapped by a layout. (We first came across layouts in *Iteration C2: Adding a Page Layout*. We'll look at them in depth starting in *Reducing Maintenance with Layouts and Partials*.) If the parameter is `false`, no layout will be applied. If set to `nil` or `true`, a layout will be applied only if there's