```
-     <%= form.label :start %>:
-     <%= form.date_select :start %>
    </p>
40:

-
-   <p>
-     <%= form.label :alarm %>:
-     <%= form.time_select :alarm %>
    </p>
45:

-   <% end %>
```

In that template, you'll see a number of labels, such as the one on line 3. You use labels to associate text with an input field for a specified attribute. The text of the label will default to the attribute name unless you specify it explicitly.

You use the `text_field` and `text_area` helpers (on lines 4 and 9, respectively) to gather single-line and multiline input fields. You may specify a `placeholder`, which will be displayed inside the field until the user provides a value. Not every browser supports this function, but those that don't simply will display an empty box. Since this will degrade gracefully, there's no need for you to design to the least common denominator—make use of this feature, because those who can see it will benefit from it immediately.

Placeholders are one of the many small "fit and finish" features provided with HTML5, and once again, Rails is ready even if the browser your users have installed is not. You can use the `search_field`, `telephone_field`, `url_field`, `email_field`, `number_field`, and `range_field` helpers to prompt for a specific type of input. How the browser will make use of this information varies. Some may display the field slightly differently to more clearly identify its function. Safari on Mac, for example, will display search fields with rounded corners and will insert a little `x` for clearing the field once data entry begins. Some may provide added validation. For example, Opera will validate URL fields prior to submission. The iPad will even adjust the