As you can see from the `bin/` prefix, this is running the `rails` command from the `bin` directory. This command is a wrapper, or *binstub*, for the Rails executable. This ensures that you're running with the correct version of every dependency.

If that doesn't work, use `bundle exec`[36] to run `rails` commands:

```
demo> bundle exec rails about
```

Once you get `bin/rails about` working, you have everything you need to start a stand-alone web server that can run our newly created Rails application. So without further ado, let's start our demo application:

```
demo> bin/dev
=> Booting Puma
=> Rails 8.0.2 application starting in development
=> Run `bin/rails server --help` for more startup options
Puma starting in single mode...
* Puma version: 6.5.0 ("Sky's Version")
* Ruby version: ruby 3.4.3 (2024-12-25 revision 48d4efcb85) +YJIT +PRISM
*  Min threads: 3
*  Max threads: 3
*  Environment: development
*          PID: 43617
* Listening on http://127.0.0.1:3000
* Listening on http://[::1]:3000
Use Ctrl-C to stop
```

Note, if you're using a virtual machine, you need to run Rails like so:

```
demo> bin/rails server -b 0.0.0.0
```

As the third line from the bottom of the startup tracing indicates, we started a web server on port 3000. The `127.0.0.1` part of the address means the Puma web server will only accept requests that originate from your machine. We can access the application by pointing a browser at the URL http://localhost:3000. The result is shown in the following screenshot.