The ActionView::Helpers::AssetTagHelper and ActionView::Helpers::UrlHelper modules contain a number of methods that let you reference resources external to the current template. Of these, the most commonly used is link_to, which creates a hyperlink to another action in your application:

```
<%= link_to "Add Comment", new_comments_path %>
```

The first parameter to link_to is the text displayed for the link. The next is a string or hash specifying the link's target.

An optional third parameter provides HTML attributes for the generated link:

```
<%= link_to "Delete", product_path(@product),
    { class: "dangerous", method: 'delete' }
%>
```

This third parameter also supports two additional options that modify the behavior of the link. Each requires JavaScript to be enabled in the browser.

The :method option is a hack—it allows you to make the link look to the application as if the request were created by a POST, PUT, PATCH, or DELETE, rather than the normal GET method. This is done by creating a chunk of JavaScript that submits the request when the link is clicked—if JavaScript is disabled in the browser, a GET will be generated.

The :data parameter allows you to set custom data attributes. The most commonly used one is the :confirm option, which takes a short message. If present, an unobtrusive JavaScript driver will display the message and get the user's confirmation before the link is followed:

```
<%= link_to "Delete", product_path(@product),
                      method: :delete,
                      data: { confirm: 'Are you sure?' }
%>
```