application using the stylesheet_link_tag and javascript_importmap_tags methods in the head:

rails80/depot_r/app/views/layouts/application.html.erb

```
<!DOCTYPE html>
<html>
  <head>
  <title><%= content_for(:title) || "Pragprog Books Online Store" %></title>
    <meta name="viewport" content="width=device-width,initial-scale=1">
    <meta name="apple-mobile-web-app-capable" content="yes">
    <meta name="mobile-web-app-capable" content="yes">
    <%= csrf_meta_tags %>
    <%= csp_meta_tag %>

    <%= yield :head %>

    <%# Enable PWA manifest for installable apps (make sure to enable in
        config/routes.rb too!) %>
    <%#= tag.link rel: "manifest", href: pwa_manifest_path(format: :json) %>

    <link rel="icon" href="/icon.png" type="image/png">
    <link rel="icon" href="/icon.svg" type="image/svg+xml">
    <link rel="apple-touch-icon" href="/icon.png">

    <%# Includes all stylesheet files in app/assets/stylesheets %>
    <%= stylesheet_link_tag :app, "data-turbo-track": "reload" %>
    <%= javascript_importmap_tags %>
  </head>
```

The javascript_importmap_tags method produces a list JavaScript filenames (assumed to live in app/javascript) which enables these resources to be imported by your application.

By default, image and style sheet assets are assumed to live in the images and stylesheets directories relative to the application's assets directory. If the path given to an asset tag method starts with a forward slash, then the path is assumed to be absolute and no prefix is applied. Sometimes it makes sense