	db2	mysql	openbase	oracle
:binary	blob(32768)	blob	object	blob
:boolean	decimal(1)	tinyint(1)	boolean	number(1)
:date	date	date	date	date
:datetime	timestamp	datetime	datetime	date
:decimal	decimal	decimal	decimal	decimal
:float	float	float	float	number
:integer	int	int(11)	integer	number(38)
:string	varchar(255)	varchar(255)	char(4096)	varchar2(255)
:text	clob(32768)	text	text	clob
:time	time	time	time	date
:timestamp	timestamp	datetime	timestamp	date

	postgresql	sqlite	sqlserver	sybase
:binary	bytea	blob	image	image
:boolean	boolean	boolean	bit	bit
:date	date	date	date	datetime
:datetime	timestamp	datetime	datetime	datetime
:decimal	decimal	decimal	decimal	decimal
:float	float	float	float(8)	float(8)
:integer	integer	integer	int	int
:string	(note 1)	varchar(255)	varchar(255)	varchar(255)
:text	text	text	text	text
:time	time	datetime	time	time
:timestamp	timestamp	datetime	datetime	timestamp

Using these tables, you could work out that a column declared to be `:integer` in a migration would have the underlying type `integer` in SQLite 3 and `number(38)` in Oracle.