substitute a caret (^) for the backslash at the end of the first line and a backslash for the forward slash in bin/rails:

```
depot> bin/rails generate scaffold Product \
         title:string description:text image_url:string price:decimal
  invoke  active_record
  create    db/migrate/20221207000001_create_products.rb
  create    app/models/product.rb
  invoke    test_unit
  create      test/models/product_test.rb
  create      test/fixtures/products.yml
  invoke  resource_route
   route    resources :products
  invoke  scaffold_controller
  create    app/controllers/products_controller.rb
  invoke    erb
  create      app/views/products
  create      app/views/products/index.html.erb
  create      app/views/products/edit.html.erb
  create      app/views/products/show.html.erb
  create      app/views/products/new.html.erb
  create      app/views/products/_form.html.erb
  create      app/views/products/_product.html.erb
  invoke    resource_route
  invoke    test_unit
  create      test/controllers/products_controller_test.rb
  create      test/system/products_test.rb
  invoke    helper
  create      app/helpers/products_helper.rb
  invoke      test_unit
  invoke    jbuilder
  create      app/views/products/index.json.jbuilder
  create      app/views/products/show.json.jbuilder
  create      app/views/products/_product.json.jbuilder
```

The generator creates a bunch of files. The one we're interested in first is the *migration* one, namely, 20221207000001_create_products.rb.

A migration represents a change we either want to make to a database as a whole or to the data contained within the database, and it's expressed in a source file in database-independent terms. These changes can update both the database schema and the data in the database tables. We apply these migrations to update our