```
»     <section class="flex">
»       <nav class="bg-green-900 p-6">
»         <ul class="text-gray-300 leading-8">
»           <li><a href="/">Home</a></li>
»           <li><a href="/questions">Questions</a></li>
»           <li><a href="/news">News</a></li>
»           <li><a href="/contact">Contact</a></li>
»         </ul>
»       </nav>
»
»       <main class="container mx-auto mt-4 px-5 flex">
          <%= yield %>
        </main>
»     </section>
    </body>
  </html>
```

Apart from the usual HTML gubbins, this layout has a number of Rails-specific items. The Rails `stylesheet_link_tag` helper method generates a `<link>` tag to both Tailwind and our application's style sheets and specifies an option to enable Turbo,[43] which transparently works behind the scenes to speed up page changes within an application.

Finally, the `csrf_meta_tags` and `csp_meta_tag` methods set up all the behind-the-scenes data needed to prevent cross-site request forgery attacks, which will be important once we add forms in Chapter 12, *Task G: Check Out!*.

Inside the body, we set the page heading to the value in the `@page_title` instance variable. By default, this is blank, meaning there won't be an `H1` rendered, but any controller that sets the variable `@page_title` can override this. The real magic, however, takes place when we invoke `yield`. This causes Rails to substitute in the page-specific content—the stuff generated by the view invoked by this request. Here, this'll be the catalog page generated by `index.html.erb`.

The page design is fairly minimal, though we've added a lot of padding, margins, and other speccing directives to ensure a decent layout for the side nav and main content. Some of the sizes we've used might seem strange (for example, `mt-4` and `px-5`), but everything should work out. Anytime we need padding, margin, or any other size, we'll use one of a few hand-picked sizes that