```
two:
  title: MyString
  description: MyText
  image_url: lorem.jpg
  price: 9.99

ruby:
  title:       Programming Ruby 1.9
  description:
    Ruby is the fastest growing and most exciting dynamic
    language out there.  If you need to get working programs
    delivered fast, you should add Ruby to your toolbox.
  price:       49.50
  image_url:   ruby.jpg
```

Maybe you noticed that the type of test that `assert_select` performs varies based on the type of the second parameter. If it's a number, it's treated as a quantity. If it's a string, it's treated as an expected result. Another useful type of test is a regular expression, which is what we use in our final assertion. We verify that there's a price that has a value that contains a dollar sign followed by any number (but at least one), commas, or digits; followed by a decimal point; followed by two digits.

One final point before we move on: both validation and functional tests will test the behavior of controllers only; they won't retroactively affect any objects that already exist in the database or in fixtures. In the previous example, two products contain the same title. Such data will cause no problems and will go undetected up to the point when such records are modified and saved.

We've touched on only a few things that `assert_select` can do. More information can be found in the online documentation.[44]

That's a lot of verification in a few lines of code. We can see that it works by rerunning just the functional tests (after all, that's all we changed):

```
depot> bin/rails test:controllers
```

Now, not only do we have something recognizable as a storefront, but we also