Iteration F2: Creating a Hotwired Cart

Turbo[53] is one of the Hotwire frameworks. Turbo lets us write code that runs in the browser and interacts with our server-based application. In our case, we'd like to make the Add to Cart buttons invoke the server `create` action on the `LineItems` controller in the background. The server can then send down just the HTML for the cart, and we can replace the cart in the sidebar with the server's updates.

Now, normally we'd do this by writing JavaScript that runs in the browser and by writing server-side code that communicates with this JavaScript (possibly using a technology such as JavaScript Object Notation [JSON]). The good news is that, with Rails, all this is hidden from us. We can use Ruby to do everything we need to do (and with a whole lot of support from some Rails helper methods).

The trick when adding Turbo to an application is to take small steps. So let's start with the most basic one. Let's change it so that our application responds with the HTML fragment containing the cart.

Because Rails includes Turbo by default, our client application is already ready. Behind the scenes it included `text/vnd.turbo-stream.html` in `Accept` header in form requests, so all we need to do is provide a turbo stream response.

We do this by adding a call to `respond_to` telling it that we want to respond with a format of `turbo_stream`:

rails7/depot_l/app/controllers/line_items_controller.rb

```
    def create
      product = Product.find(params[:product_id])
      @line_item = @cart.add_product(product)

      respond_to do |format|
        if @line_item.save
»         format.turbo_stream do
»           render turbo_stream: turbo_stream.replace(
»             :cart,
```