```
»             partial: 'layouts/cart',
»             locals: { cart: @cart }
»           )
»         end
          format.html { redirect_to store_index_url }
          format.json { render :show,
            status: :created, location: @line_item }
        else
          format.html { render :new,
            status: :unprocessable_entity }
          format.json { render json: @line_item.errors,
            status: :unprocessable_entity }
        end
      end
    end
```

The way to read this code is as follows: whenever we get a request that accepts a turbo stream response, we render a turbo stream response consisting of turbo stream replace, specifying an HTML element ID of cart as the element to be replaced, and rendering the partial, which can be found in `app/views/application/_cart.html.erb` using the value of `@cart` as the value of `cart`.

When receiving a turbo stream response, Turbo instructs the browser to stick the HTML fragment contained in the response into the browser's internal representation of the structure and content of the document being displayed—namely, the Document Object Model (DOM). By manipulating the DOM, we cause the display to change in front of the user's eyes.

Best of all, if the browser's request does *not* specify that it will accept a turbo stream response (perhaps because JavaScript was disabled?), what it will get instead is the HTML response, which in this case is a redirect to the store.

Now let's create the partial that this code references. Starting with code we extract from `app/views/layouts/application.html.erb`, add an HTML `id` attribute so that Turbo can identify the portion of the display that needs to be replaced. As we do this, we take care to ensure that the `id` is present even when the cart isn't displayed, which we do by adding an `else` clause:

rails7/depot_m/app/views/layouts/_cart.html.erb