```
<% if cart and not cart.line_items.empty? %>
  <div id="cart" class="bg-white rounded p-2">
    <%= render cart %>
  </div>
<% else %>
  <div id="cart"></div>
<% end %>
```

Finally, we update the template that we extracted this from to make use of the new partial:

rails7/depot_m/app/views/layouts/application.html.erb

```
<!DOCTYPE html>
<html>
  <head>
    <title>Pragprog Books Online Store</title>
    <meta name="viewport" content="width=device-width,initial-scale=1">
    <%= csrf_meta_tags %>
    <%= csp_meta_tag %>
    <%= stylesheet_link_tag "inter-font", "data-turbo-track": "reload" %>
    <%= stylesheet_link_tag "tailwind", "data-turbo-track": "reload" %>

    <%= stylesheet_link_tag "application", "data-turbo-track": "reload" %>
    <%= javascript_importmap_tags %>
  </head>

  <body>
    <header class="bg-green-700">
      <%= image_tag 'logo.svg', alt: 'The Pragmatic Bookshelf' %>
      <h1><%= @page_title %></h1>
    </header>

    <section class="flex">
      <nav class="bg-green-900 p-6">
»       <%= render partial: 'layouts/cart', locals: {cart: @cart } %>


        <ul class="text-gray-300 leading-8">
          <li><a href="/">Home</a></li>
          <li><a href="/questions">Questions</a></li>
          <li><a href="/news">News</a></li>
          <li><a href="/contact">Contact</a></li>
        </ul>
```