What's important here is the name of the class (`ProductsChannel`) and the name of the stream (`products`). It's possible for a channel to support multiple streams (for example, a chat application can have multiple rooms), but we only need one stream for now.

Channels can have security implications, so by default Rails only allows access from the localhost when running in development mode. If you're doing development with multiple machines, you must disable this check. Do this by uncommenting the following line in `config/environments/development.rb`:

```
config.action_cable.disable_request_forgery_protection = true
```

We'll be sending only data over this channel, and not processing commands, so this is safe to do.

As with before, we begin by separating out the product information from the store index template into a partial, and wrapping it with an HTML element with an `id` attribute.

rails7/depot_o/app/views/store/_product.html.erb

```
» <%= turbo_frame_tag(dom_id(product)) do %>
    <li class='flex mb-6'>
      <%= image_tag(product.image_url,
        class: 'object-contain w-40 h-48 shadow mr-6') %>

      <div>
        <h2 class="font-bold text-lg mb-3"><%= product.title %></h2>

        <p>
          <%= sanitize(product.description) %>
        </p>

        <div class="mt-3">
          <%= number_to_currency(product.price) %>

          <%= button_to 'Add to Cart',
              line_items_path(product_id: product),
              form_class: 'inline',
              class: 'ml-4 rounded-lg py-1 px-2
                      text-white bg-green-600' %>
```