```
            notice: "Product was successfully updated." }
          format.json { render :show, status: :ok, location: @product }
»
»         @product.broadcast_replace_later_to 'products',
»           partial: 'store/product'
        else
          format.html { render :edit,
            status: :unprocessable_entity }
          format.json { render json: @product.errors,
            status: :unprocessable_entity }
        end
      end
    end
```

We're calling `broadcast_replace_later_to` because we want the messages to go out asynchronously, and generally after this request completes. We specify the channel and the partial to be used.

To start the Action Cable process (and to pick up the configuration change if that was done), we need to restart the server. The first time you visit the Depot page you'll see additional messages on the server window (information slightly abbreviated to fit within the book margins):

```
Started GET "/cable" for 127.0.0.1
Started GET "/cable/" [WebSocket] for 127.0.0.1
Successfully upgraded to WebSocket
Started GET "/cable" for 127.0.0.1
ProductsChannel is transmitting the subscription confirmation
ProductsChannel is streaming from products
Started GET "/cable/" [WebSocket] for 127.0.0.1
Successfully upgraded to WebSocket
Turbo::StreamsChannel is transmitting the subscription confirmation
Turbo::StreamsChannel is streaming from products
```

Again, update the price of a book in one browser window and watch the catalog update instantly in any other browser window that shows the Depot store.

Should you have difficulties, check these:

- If you have redis installed, ensure it is running by issuing the following command: