```
    <h2 class="font-bold text-lg mb-3">Your Cart</h2>

    <table class="table-auto">
      <%= render cart.line_items %>

      <tfoot>
        <tr>
          <th class="text-right pr-2 pt-2" colspan="3">Total:</th>
          <td class="text-right pt-2 font-bold border-t-2 border-black">
            <%= number_to_currency(cart.total_price) %>
          </td>
        </tr>
      </tfoot>
    </table>

»   <div class="flex mt-1">
      <%= button_to 'Empty Cart', cart, method: :delete,
        class: 'ml-4 rounded-lg py-1 px-2 text-white bg-green-600' %>

»     <%= button_to 'Checkout', new_order_path, method: :get,
»       class: 'ml-4 rounded-lg py-1 px-2 text-black bg-green-200' %>
»   </div>
  </div>
```

We wrapped the buttons in a `div` and used a flex layout so that they'll appear side by side.

The first thing we want to do is check to make sure that there's something in the cart. This requires us to have access to the cart. Planning ahead, we'll also need this when we create an order:

rails7/depot_o/app/controllers/orders_controller.rb

```
  class OrdersController < ApplicationController
»   include CurrentCart
»   before_action :set_cart, only: %i[ new create ]
»   before_action :ensure_cart_isnt_empty, only: %i[ new ]
    before_action :set_order, only: %i[ show edit update destroy ]

    # GET /orders or /orders.json
    #...
»
»   private
```