```
»       assert has_no_field? 'Routing number'
»       assert has_no_field? 'Account number'
»       assert has_no_field? 'Credit card number'
»       assert has_no_field? 'Expiration date'
»       assert has_no_field? 'Po number'
»
»       select 'Check', from: 'Pay type'
»
»       assert has_field? 'Routing number'
»       assert has_no_field? 'Account number'
»       assert has_no_field? 'Credit card number'
»       assert has_no_field? 'Expiration date'
»       assert has_no_field? 'Po number'
»
»       select 'Credit card', from: 'Pay type'
»
»       assert has_no_field? 'Routing number'
»       assert has_no_field? 'Account number'
»       assert has_field? 'Credit card number'
»       assert has_field? 'Expiration date'
»       assert has_no_field? 'Po number'
»
»       select 'Purchase order', from: 'Pay type'
»
»       assert has_no_field? 'Routing number'
»       assert has_no_field? 'Account number'
»       assert has_no_field? 'Credit card number'
»       assert has_no_field? 'Expiration date'
»       assert has_field? 'Po number'
»     end
    end
```

As you can see, it's largely a repetition of a few lines of code with minor variations, prefaced by a few discrete steps: `visit` a URL, find the `:first` button with the text `"Add to Cart"` and `click_on` it. Then `click_on` the button labeled `"Checkout"`. We then `select` various pay types and verify what fields we expect to see and what fields we expect *not* to see.

At this point in the test, we check an assumption that the routing number field is not on the page yet. We do this using `has_no_field?` and pass it `"Routing number"`, which is a the text the user would see if they had selected Check as the Pay type. We repeat this for all the other fields that the user could eventually see but at this