The `:sendmail` setting delegates mail delivery to your local system's `sendmail` program, which is assumed to be in `/usr/sbin`. This delivery mechanism isn't particularly portable, because `sendmail` isn't always installed in this directory for every operating system. It also relies on your local `sendmail` supporting the `-i` and `-t` command options.

You achieve more portability by leaving this option at its default value of `:smtp`. If you do so, you'll need also to specify some additional configuration to tell Action Mailer where to find an SMTP server to handle your outgoing email. This can be the machine running your web application, or it can be a separate box (perhaps at your ISP if you're running Rails in a noncorporate environment). Your system administrator will be able to give you the settings for these parameters. You may also be able to determine them from your own mail client's configuration.

The following are typical settings for Gmail: adapt them as you need.

```
Rails.application.configure do
  config.action_mailer.delivery_method = :smtp

  config.action_mailer.smtp_settings = {
    address:        "smtp.gmail.com",
    port:           587,
    domain:         "domain.of.sender.net",
    authentication: "plain",
    user_name:      "dave",
    password:       "secret",
    enable_starttls_auto: true
  }
end
```

As with all configuration changes, you'll need to restart your application if you make changes to any of the environment files.

Sending Email

Now that we have everything configured, let's write some code to send emails.

By now you shouldn't be surprised that Rails has a generator script to create