```
    def destroy
»     session[:user_id] = nil
»     redirect_to store_index_url, notice: "Logged out"
    end
```

Finally, it's about time to add the index page—the first screen that administrators see when they log in. Let's make it useful. We'll have it display the total number of orders in our store. Create the template in the `index.html.erb` file in the `app/views/admin` directory. (This template uses the `pluralize` helper, which in this case generates the `order` or `orders` string, depending on the cardinality of its first parameter.)

rails7/depot_r/app/views/admin/index.html.erb

```
<div class="w-full">
  <h1 class="mx-auto text-lg font-bold text-4xl">Welcome</h1>

  <p>
    It's <%= Time.now %>.
    We have <%= pluralize(@total_orders, "order") %>.
  </p>
</div>
```

The `index` action sets up the count:

rails7/depot_r/app/controllers/admin_controller.rb

```
class AdminController < ApplicationController
  def index
»     @total_orders = Order.count
  end
end
```

We have one more task to do before we can use this. Whereas previously we relied on the scaffolding generator to create our model and routes for us, this time we simply generated a controller because there's no database-backed model for this controller. Unfortunately, without the scaffolding conventions to guide it, Rails has no way of knowing which actions are to respond to `GET` requests, which are to respond to `POST` requests, and so on, for this controller. We need to provide this information by editing our `config/routes.rb` file: