Iteration J1: Selecting the Locale

We start by creating a new configuration file that encapsulates our knowledge of what locales are available and which one is to be used as the default:

rails7/depot_t/config/initializers/i18n.rb

```
#encoding: utf-8
I18n.default_locale = :en

LANGUAGES = [
  ['English',                  'en'],
  ["Espa&ntilde;ol".html_safe, 'es']
]
```

This code is doing two things.

The first thing it does is use the `I18n` module to set the default locale. `I18n` is a funny name, but it sure beats typing out *internationalization* all the time. Internationalization, after all, starts with an *i*, ends with an *n*, and has eighteen letters in between.

Then the code defines a list of associations between display names and locale names. Unfortunately, all we have available at the moment is a U.S. keyboard, and Español has a character that can't be directly entered via our keyboard. Different operating systems have different ways of dealing with this, and often the easiest way is to copy and paste the correct text from a website. If you do this, make sure your editor is configured for UTF-8. Meanwhile, we've opted to use the HTML equivalent of the *n con tilde* character in Spanish. If we didn't do anything else, the markup itself would be shown. But by calling `html_safe`, we inform Rails that the string is safe to be interpreted as containing HTML.

For Rails to pick up this configuration change, the server needs to be restarted.

Since each page that's translated will have an `en` and an `es` version (for now—more will be added later), it makes sense to include this in the URL. Let's plan to put the locale up front, make it optional, and have it default to the current locale,