```
-- create_table(:action_mailbox_inbound_emails)
   -> 0.0017s
== 20221207191847 CreateActionMailboxTables: migrated (0.0017s) =============
```

In the real world, we'd also need to configure Action Mailbox for our particular incoming email service provider. The Rails Guide[76] is the best place to look for how to do that. We won't set one up here since setting up accounts with services like Amazon SES or Mailgun is somewhat involved (though once you have your account set up, configuring Rails to use it is a snap). For our immediate needs, Rails provides a way to simulate sending emails, which we'll see in a moment.

The way Action Mailbox works is that all incoming emails get stored in a cloud storage system like Amazon's S3. Rails includes a library called Active Storage that abstracts away the details of the cloud service you're using. We'll need to configure Active Storage for Action Mailbox to work properly.

Setting up Active Storage

As with your real-world email provider, your real-world cloud storage provider will require specific configuration in Rails, and the Guide[77] can give you the details. For our purposes, we'll set up the disk-based service that works with our local disk. This will allow us to fully use Active Storage locally, which means Action Mailbox can work locally.

To set that up, we'll need to configure the service in our app's configuration and then tell Rails where to store the files that Active Storage will manage.

First, edit config/environments/development.rb, adding this line to the configuration at the end of the block:

rails7/depot_ua/config/environments/development.rb

```
» config.active_storage.service = :local
end
```

We will explain what :local means in a moment. Now, add a similar line to config/environments/test.rb but using the :test service instead: