rails7/depot_ua/config/environments/test.rb

```
»   config.active_storage.service = :test
  end
```

With those added, we must now define what those symbols mean by creating config/storage.yml to look like so:

rails7/depot_ua/config/storage.yml

```
» local:
»   service: Disk
»   root: <%= Rails.root.join("storage") %>
»
» test:
»   service: Disk
»   root: <%= Rails.root.join("tmp/storage") %>
```

The root key in this file should match the values we used in the files in config/environments. In this case, we've configured both :local and :test to use Active Storage's disk-based service, with our development environment (:local) using the directory storage that's in the root of our project and the test environment (:test) using tmp/storage.

With this set up, when we receive an email, the entire payload gets written to our storage service and, as we'll see in a moment, we can access parts of that email to trigger whatever logic we need in our Rails app. The reason Rails does this is that emails can be large (especially if they have attachments), and you don't necessarily want to store very large objects in a relational database. It's much more common to store such data to disk or with a cloud storage provider and store a reference to that object in the database.

Now that we've done the one-time setup, let's create a mailbox to receive our support request emails from customers.

Creating a Mailbox to Receive Emails

Action Mailbox works by routing incoming emails to a mailbox. A mailbox is a subclass of ApplicationMailbox with a method named process that is called for each