email routed to that mailbox. The way emails get routed is similar to how web requests get routed in config/routes.rb. For email, you'll tell Rails what sorts of emails you want routed where.

We want emails to support@example.com to get routed to a mailbox so we can handle them. The way to do that is to insert a call to the method routing inside ApplicationMailbox, like so:

rails7/depot_ua/app/mailboxes/application_mailbox.rb

```
  class ApplicationMailbox < ActionMailbox::Base
»   routing "support@example.com" => :support
  end
```

This tells Rails that any email to (or cc'd to) support@example.com should be handled by the class SupportMailbox. We can create that class using a Rails generator like so:

```
> bin/rails generate mailbox support
      create  app/mailboxes/support_mailbox.rb
      invoke  test_unit
      create    test/mailboxes/support_mailbox_test.rb
```

If you look at app/mailboxes/support_mailbox.rb, you'll see a few lines of code, notably an empty method called process:

```
class SupportMailbox < ApplicationMailbox
  def process
  end
end
```

Now, every email we receive at support@example.com will trigger a call to process in SupportMailbox. Inside the process method, we have access to the special variable mail. This is an instance of Mail::Message[78] and allows us to access the various bits of an email you might expect to have, such as who sent it, the subject, and the contents.

Let's see how this works before getting too far along by adding some puts calls into our mailbox: