together.

Note that starting with macOS Catalina, the default shell is zsh, not bash as it had been historically. Assuming you're using either Catalina or Monterey and zsh, the Homebrew setup is as follows:

```
$ brew install rbenv ruby-build
$ rbenv init
$ echo 'eval "$(rbenv init -)"' >> ~/.zshrc
$ rehash
```

On older versions of macOS (or if you are using bash on Catalina or Monterey), the instructions are similar:

```
$ brew install rbenv ruby-build
$ echo 'export PATH="$HOME/.rbenv/bin:$PATH"' >> ~/.bash_profile
$ ~/.rbenv/bin/rbenv init
$ hash -r
```

Once you've done that, restart your terminal by typing `exit` and hitting `Return` and then opening a new terminal window. After that, you can install Ruby like so:

```
$ rbenv install 3.1.3
$ rbenv global 3.1.3
```

If you had previously installed `ruby-build` and it can't find the definition for Ruby 3.1.3, you might need to reinstall `ruby-build` and try again:

```
$ brew reinstall --HEAD ruby-build
$ rbenv install 3.1.3
$ rbenv global 3.1.3
```

These are the two most popular routes for Mac developers. RVM and chruby are two other alternatives.[16][17]

Whichever path you take, run the following command to see which version of Ruby you're working with:

```
$ ruby -v
```