```
RUN rm /etc/nginx/sites-enabled/default
RUN rm -f /etc/service/nginx/down
RUN rm -f /etc/service/redis/down
ADD config/nginx.conf /etc/nginx/sites-enabled/depot.conf

USER app
RUN mkdir /home/app/depot
WORKDIR /home/app/depot

ENV RAILS_ENV=production
ENV BUNDLE_WITHOUT="development test"
COPY --chown=app:app Gemfile Gemfile.lock .
RUN bundle install
COPY --chown=app:app . .

RUN SECRET_KEY_BASE=`bin/rails secret` \
  bin/rails assets:precompile

USER root
CMD ["/sbin/my_init"]
```

This is remarkably short, and that's because we can start with a pre-build image as a starting point. Phusion provides a number of images that you can build upon.[87] We chose `full` because it includes everything we need. Other images provide different versions of Ruby, and those are "some assembly required" starters.

Before proceeding, feel free to look around the image by running the command provided:[88]

```
$ docker run --rm -t -i phusion/passenger-full bash -l
```

This particular image provides an initialization script (`/sbin/my_init`) and is designed to be configured by removing and adding files. We proceed to remove the default site, enable `nginx` and `redis`, and provide our own site definition:

rails7/depot_td/config/nginx.conf

```
server {
    listen 80;
    server_name www.depot.com;
```