```
    root /home/app/depot/public;

    passenger_enabled on;
    passenger_user app;
    passenger_ruby /usr/bin/ruby;

    location /cable {
        passenger_app_group_name /home/app/depot/cable;
        passenger_force_max_concurrent_requests_per_process 0;
    }
}
```

This file starts by giving the web port and server name and identifying where static files that can be served by the web server itself can be found. Then it enables passenger and tells it what Unix user to use to run this app and where the **ruby** executable can be found. Finally, it configures Action Cable, which passenger runs in a separate process and allows an unlimited number of simultaneous requests. More information on this can be found in the documentation.[89]

We return to the **Dockerfile**, specifically looking at the portion creating the application:

rails7/depot_td/Dockerfile

```
USER app
RUN mkdir /home/app/depot
WORKDIR /home/app/depot

ENV RAILS_ENV=production
ENV BUNDLE_WITHOUT="development test"
COPY --chown=app:app Gemfile Gemfile.lock .
RUN bundle install
COPY --chown=app:app . .

RUN SECRET_KEY_BASE=`bin/rails secret` \
  bin/rails assets:precompile
```

Most of this is very straightfoward: the user is set, and a directory is created and set as the current working directory. The Rails environment is set to **production**, the code is copied to the image, and **bundle install** is run. Note that the **Gemfile** is