directory or a subdirectory of it. Locate wherever that is and create `Vagrantfile` to have the following contents (comments in the code explain what each bit does, if you're curious):

```
# We want to use version '2' of Vagrant's configuration language
Vagrant.configure("2") do |config|

  # This is the operating system to use, in this case
  # Ubuntu Linux
  config.vm.box = "ubuntu/jammy64"

  # This is configuration specifically for the virtual
  # machine, and this gives it 4G of memory
  config.vm.provider "virtualbox" do |vb|
    vb.memory = "4096"
  end

  # When Rails runs on port 3000 inside your virtual machine, this
  # allows you to access it from a browser on your machine by
  # going to port 3000 on your machine.
  config.vm.network "forwarded_port", guest: 3000, host: 3000

  # This will mount your current directory on your computer
  # to the directory /files_on_your_computer inside the virtual machine
  config.vm.synced_folder ".", "/files_on_your_computer"
end
```

If you aren't in a command-line window at this point, open one up and change to the directory where you created this file. Then bring up the machine with the following command:

```
$ vagrant up
```

The very first time, it'll take a while for this command to complete. It has to download and install an entire operating system, so be patient. When it's done, you can log in to the virtual machine, like so:

```
$ vagrant ssh
```

You're now logged in to your virtual machine, so we can now start installing the software you'll need to learn Rails.