server
: Runs your Rails application in a self-contained web server, using the web server listed in your `Gemfile`, or WEBrick if none is listed. We've been using Puma in our Depot application during development.

A Place for Temporary Files

It probably isn't a surprise that Rails keeps its temporary files tucked in the `tmp` directory. You'll find subdirectories for cache contents, sessions, and sockets in here. Generally these files are cleaned up automatically by Rails, but occasionally if things go wrong, you might need to look in here and delete old files.

A Place for Third-Party Code

The `vendor` directory is where third-party code lives. You can install Rails and all of its dependencies into the `vendor` directory.

If you want to go back to using the system-wide version of gems, you can delete the `vendor/cache` directory.

A Place for Configuration

The `config` directory contains files that configure Rails. In the process of developing Depot, we configured a few routes, configured the database, created an initializer, modified some locales, and defined deployment instructions. The rest of the configuration was done via Rails conventions.

Before running your application, Rails loads and executes `config/environment.rb` and `config/application.rb`. The standard environment set up automatically by these files includes the following directories (relative to your application's base directory) in your application's load path:

- The `app/controllers` directory and its subdirectories
- The `app/models` directory
- The `vendor` directory and the `lib` contained in each `plugin` subdirectory
- The directories `app`, `app/helpers`, `app/mailers`, and `app/*/concerns`