Renders a template and arranges for the resulting text to be sent back to the client. The `:template` value must contain both the controller and action parts of the new name, separated by a forward slash. The following code will render the template `app/views/blog/short_list`:

```
class BlogController < ApplicationController
  def index
    render(template: "blog/short_list")
  end
end
```

render(file: path)

Renders a view that may be entirely outside of your application (perhaps one shared with another Rails application). By default, the file is rendered without using the current layout. This can be overridden with `layout: true`.

render(partial: name, ...)

Renders a partial template. We talk about partial templates in depth in *Partial-Page Templates*.

render(nothing: true)

Returns nothing—sends an empty body to the browser.

render(xml: stuff)

Renders *stuff* as text, forcing the content type to be `application/xml`.

render(json: stuff, [callback: hash])

Renders *stuff* as JSON, forcing the content type to be `application/json`. Specifying `:callback` will cause the result to be wrapped in a call to the named callback function.

render(:update) do |page| ... end

Renders the block as an RJS template, passing in the page object.

```
render(:update) do |page|
  page[:cart].replace_html partial: 'cart', object: @cart
  page[:cart].visual_effect :blind_down if @cart.total_items == 1
end
```

All forms of `render` take optional `:status`, `:layout`, and `:content_type` parameters. The