```
10: </p>
 -
 -  <p>
 -    <%= form.label :color %>:
 -    <%= form.radio_button :color, 'red' %>
15:    <%= form.label :red %>
 -    <%= form.radio_button :color, 'yellow' %>
 -    <%= form.label :yellow %>
 -    <%= form.radio_button :color, 'green' %>
 -    <%= form.label :green %>
20: </p>
 -
 -  <p>
 -    <%= form.label 'condiment' %>:
 -    <%= form.check_box :ketchup %>
25:    <%= form.label :ketchup %>
 -    <%= form.check_box :mustard %>
 -    <%= form.label :mustard %>
 -    <%= form.check_box :mayonnaise %>
 -    <%= form.label :mayonnaise %>
30: </p>
 -
 -  <p>
 -    <%= form.label :priority %>:
 -    <%= form.select :priority, (1..10) %>
35: </p>
 -
 -  <p>
 -    <%= form.label :start %>:
 -    <%= form.date_select :start %>
40: </p>
 -
 -  <p>
 -    <%= form.label :alarm %>:
 -    <%= form.time_select :alarm %>
45: </p>
 -  <% end %>
```

In that template, you'll see a number of labels, such as the one on line 3. You use labels to associate text with an input field for a specified attribute. The text of the label will default to the attribute name unless you specify it explicitly.

You use the `text_field` and `text_area` helpers (on lines 4 and 9, respectively) to