There's a method to pluralize nouns:

```
<%= pluralize(1, "person") %> but <%= pluralize(2, "person") %>
```

```
1 person but 2 people
```

If you'd like to do what the fancy websites do and automatically hyperlink URLs and email addresses, there are helpers to do that. Another one strips hyperlinks from text.

Back in Iteration A2, we saw how the `cycle` helper can be used to return the successive values from a sequence each time it's called, repeating the sequence as necessary. This is often used to create alternating styles for the rows in a table or list. The `current_cycle` and `reset_cycle` methods are also available.

Finally, if you're writing something like a blog site or you're allowing users to add comments to your store, you could offer them the ability to create their text in Markdown (BlueCloth)[112] or Textile (RedCloth)[113] format. These are formatters that take text written in human-friendly markup and convert it into HTML.

Linking to Other Pages and Resources

The `ActionView::Helpers::AssetTagHelper` and `ActionView::Helpers::UrlHelper` modules contain a number of methods that let you reference resources external to the current template. Of these, the most commonly used is `link_to`, which creates a hyperlink to another action in your application:

```
<%= link_to "Add Comment", new_comments_path %>
```

The first parameter to `link_to` is the text displayed for the link. The next is a string or hash specifying the link's target.

An optional third parameter provides HTML attributes for the generated link:

```
<%= link_to "Delete", product_path(@product),
    { class: "dangerous", method: 'delete' }
%>
```

This third parameter also supports two additional options that modify the