```
      <%= link_to_unless_current(action.capitalize, action: action) %>
    </li>
  <% end %>
  </ul>
```

The `link_to_unless_current` helper may also be passed a block that's evaluated only if the current action is the action given, effectively providing an alternative to the link. There's also a `current_page` helper method that simply tests whether the current page was generated by the given options.

As with `url_for`, `link_to` and friends also support absolute URLs:

```
<%= link_to("Help", "http://my.site/help/index.html") %>
```

The `image_tag` helper creates `<img>` tags. Optional `:size` parameters (of the form *width*`x`*height*) or separate width and height parameters define the size of the image:

```
<%= image_tag("/assets/dave.png", class: "bevel", size: "80x120") %>
<%= image_tag("/assets/andy.png", class: "bevel",
              width: "80", height: "120") %>
```

If you don't give an `:alt` option, Rails synthesizes one for you using the image's filename. If the image path doesn't start with a / character, Rails assumes that it lives under the `app/assets/images` directory.

You can make images into links by combining `link_to` and `image_tag`:

```
<%= link_to(image_tag("delete.png", size: "50x22"),
            product_path(@product),
            data: { confirm: "Are you sure?" },
            method: :delete)
%>
```

The `mail_to` helper creates a `mailto:` hyperlink that, when clicked, normally loads the client's email application. It takes an email address, the name of the link, and a set of HTML options. Within these options, you can also use `:bcc`, `:cc`, `:body`, and `:subject` to initialize the corresponding email fields. Finally, the magic option `encode: "javascript"` uses client-side JavaScript to obscure the generated link,