making it harder for spiders to harvest email addresses from your site. Unfortunately, it also means your users won't see the email link if they have JavaScript disabled in their browsers.

```
<%= mail_to("support@pragprog.com", "Contact Support",
            subject: "Support question from #{@user.name}",
            encode:  "javascript") %>
```

As a weaker form of obfuscation, you can use the `:replace_at` and `:replace_dot` options to replace the at sign and dots in the displayed name with other strings. This is unlikely to fool harvesters.

The `AssetTagHelper` module also includes helpers that make it easy to link to style sheets and JavaScript code from your pages and to create autodiscovery Atom feed links. We created links in the layouts for the Depot application using the `stylesheet_link_tag` and `javascript_importmap_tags` methods in the head:

rails7/depot_r/app/views/layouts/application.html.erb

```
<!DOCTYPE html>
<html>
  <head>
    <title>Pragprog Books Online Store</title>
    <meta name="viewport" content="width=device-width,initial-scale=1">
    <%= csrf_meta_tags %>
    <%= csp_meta_tag %>
    <%= stylesheet_link_tag "inter-font", "data-turbo-track": "reload" %>
    <%= stylesheet_link_tag "tailwind", "data-turbo-track": "reload" %>

    <%= stylesheet_link_tag "application", "data-turbo-track": "reload" %>
    <%= javascript_importmap_tags %>
  </head>
```

The `javascript_importmap_tags` method produces a list JavaScript filenames (assumed to live in `app/javascript`) which enables these resources to be imported by your application.

By default, image and style sheet assets are assumed to live in the `images` and `stylesheets` directories relative to the application's `assets` directory. If the path given to an asset tag method starts with a forward slash, then the path is assumed