```
  it "has a total price of the two items' price" do
    expect(cart.total_price).to eq(book_one.price + book_two.price)
  end
```

These assertions won't succeed unless items are added to the cart first. That code *could* go inside each example, but RSpec allows you to extract duplicate setup code into a block using `before`:

```
  before do
    cart.add_product(book_one).save!
    cart.add_product(book_two).save!
  end
  it "has two line items" do
    expect(cart.line_items.size).to eq(2)
  end
  it "has a total price of the two items' price" do
    expect(cart.total_price).to eq(book_one.price + book_two.price)
  end
```

This setup is only relevant to some of the tests of the `add_product` method, specifically the tests around adding different items. To test adding the same item twice, you'll need different setups. To make this happen, wrap the above code in a block using `context`. `context` takes a string that describes the context we're creating and acts as a scope for `before` blocks. It's also customary to wrap all examples of the behavior of a method inside a block given to `describe`.

Given all that, here's what the first half of your spec should look like:

rails7/depot_xa/spec/models/cart_spec.rb

```
» describe "#add_product" do
»   context "adding unique products" do
»     before do
»       cart.add_product(book_one).save!
»       cart.add_product(book_two).save!
»     end
»
»     it "has two line items" do
»       expect(cart.line_items.size).to eq(2)
»     end
»     it "has a total price of the two items' price" do
»       expect(cart.total_price).to eq(book_one.price + book_two.price)
```