```
The article was saved and now the user is going to be redirected...
```

```
Redirected to http://localhost:3000/articles/1
```

```
Completed 302 Found in 4ms (ActiveRecord: 0.8ms)
```

Adding extra logging like this makes it easy to search for unexpected or unusual behavior in your logs. If you add extra logging, be sure to make sensible use of log levels to avoid filling your production logs with useless trivia.

2.4 Tagged Logging

When running multi-user, multi-account applications, it's often useful to be able to filter the logs using some custom rules. TaggedLogging in Active Support helps you do exactly that by stamping log lines with subdomains, request ids, and anything else to aid debugging such applications.

```
logger = ActiveSupport::TaggedLogging.new(Logger.new(STDOUT))
logger.tagged("BCX") { logger.info "Stuff" }
# Logs "[BCX] Stuff"
logger.tagged("BCX", "Jason") { logger.info "Stuff" }

# Logs "[BCX] [Jason] Stuff"
logger.tagged("BCX") { logger.tagged("Jason") { logger.info "Stuff" } } # Logs "[BCX] [Jason] Stuff"
logger = ActiveSupport::TaggedLogging.new(Logger.new(STDOUT))
logger.tagged("BCX") { logger.info "Stuff" }

# Logs "[BCX] Stuff"
logger.tagged("BCX", "Jason") { logger.info "Stuff" } # Logs "[BCX] [Jason] Stuff"

logger.tagged("BCX") { logger.tagged("Jason") { logger.info "Stuff" } } # Logs "[BCX] [Jason] Stuff"
```

Impact of Logs on Performance