```
  set         -- Modifies byebug settings
  show        -- Shows byebug settings
  source      -- Restores a previously saved byebug session
  step        -- Steps into blocks or methods one or more
times
  thread      -- Commands to manipulate threads
  tracevar    -- Enables tracing of a global variable
  undisplay   -- Stops displaying all or some expressions when
program stops
  untracevar -- Stops tracing a global variable
  up          -- Moves to a higher frame in the stack trace
  var         -- Shows variables and its values
  where       -- Displays the backtrace
```

Step 5

The display command evaluates expressions every time the debugger stops.

```
(byebug) info display
There are no auto-display expressions now.
```

Doing a info on line gives you the line number of the current break point.

```
(byebug) info line
Line 8 of "/Users/bparanj/projects/blog5/app/controllers/
tasks_controller.rb"
```

Step 6

You can inspect variable by printing them.

```
 p @tasks
  Task Load (2.5ms)  SELECT "tasks".* FROM "tasks"
#<ActiveRecord::Relation [#<Task id: 1, name: "Get rich
quick", complete: true, created_at: "2016-03-18 21:37:57",
updated_at: "2016-03-24 01:12:25", project_id: 1, priority:
4, due_date: "2016-01-18 21:37:57">, #<Task id: 2, name:
"Write a book", complete: true, created_at: "2016-03-18
21:37:57", updated_at: "2016-03-18 21:37:57", project_id: 1,
p...
```

Step 7

The step command steps into blocks or methods one or more times.

```
(byebug) step
```