```
-- Enables breakpoints or displays
-- Runs the program until frame returns
-- Moves to a frame in the call stack
-- Helps you using byebug
-- Shows byebug's history of commands
-- Shows several informations about the program being
debugged
  interrupt  -- Interrupts the program
  irb        -- Starts an IRB session
  kill       -- Sends a signal to the current process
  list       -- Lists lines of source code
  method     -- Shows methods of an object, class or module
  next       -- Runs one or more lines of code
  pry        -- Starts a Pry session
  quit       -- Exits byebug
  restart    -- Restarts the debugged program
  save       -- Saves current byebug session to a file
  set        -- Modifies byebug settings
  show       -- Shows byebug settings
  source     -- Restores a previously saved byebug session
  step       -- Steps into blocks or methods one or more times
  thread     -- Commands to manipulate threads
  tracevar   -- Enables tracing of a global variable
  undisplay  -- Stops displaying all or some expressions when program
stops
  untracevar -- Stops tracing a global variable
  up         -- Moves to a higher frame in the stack trace
  var        -- Shows variables and its values
  where      -- Displays the backtrace
(byebug)
```

To see the previous ten lines you should type list- (or l-).

```
(byebug) l-

[1, 10] in /PathTo/project/app/controllers/articles_controller.rb
   1  class ArticlesController < ApplicationController
   2    before_action :set_article, only: [:show, :edit, :update,
```